Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump space heater		No label found for faw.heatpump.single	GT-SKR030KBDC-S32
Space Heating	Energy efficiency class 55°C (High temp. app.)		A++
Average climate (Design temperature = -10°C)	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Space heating 55°C	Prated (declared heating capacity) @ -10°C	[kW]	7.95
	Seasonal space heating efficiency (η_S)	[%]	134
	Annual energy consumption	[kWh]	4776
Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	7.71
	Seasonal space heating efficiency (n _S)	[%]	179.7
	Annual energy consumption	[kWh]	3486
off peak operation function integrated in Heat pump	Annual energy consumption	Y/N	N
Colder climate (Design temperature = -22°C) Space heating 55°C		[kW]	6.95
	Prated (declared heating capacity) @ -22°C		
	Seasonal space heating efficiency (η_S)	[%]	104
Space heating 35°C Warmer climate (Design temperature = 2°C)	Annual energy consumption	<u>[kWh]</u> [kW]	5342 6.71
	Prated (declared heating capacity) @ -22°C		
	Seasonal space heating efficiency (η_S)	[%]	140.2
	Annual energy consumption	[kWh]	3872
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	9.95
		[%]	174
	Seasonal space heating efficiency (n _S)		
Space heating 35°C Sound Power (*)	Annual energy consumption	[kWh] [kW]	4640 9.71
	Prated (declared heating capacity) @ 2°C	[%]	233.6
	Seasonal space heating efficiency (η_S)		
	Annual energy consumption	[kWh] [dB(A)]	3391 61
Ecodesign technical data			
Product description	Air-to-water heat pump:	Y/N M/N	Yes
	Water-to-water heat pump: Brine-to-water heat pump:	<u>Y/N</u> Y/N	No No
	Low-temperature heat pump:	Y/N	No
	Equipped with a supplementary heater: For heat pump combination heater:	<u>Y/N</u> Y/N	No No
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3300
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control		Inverter
	P _{Off} (Power consumption Off mode)	[kW]	0.020
	P _{1O} (Power consumption Thermostat off mode)	[kW]	0.020
		[kW]	0.020
	P _{Sb} (Power consumption Standby mode)		0.038
	PCK (Power crankcase heater model)	[kW]	0.038
	Q _{Elec} (Daily electricity consumption)	[kWh]	/
	Q _{fUC} (Daily fuel consumption)	[kWh]	/
Part load conditions space heating average climate	1001		
A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	6.82
· · · · · · · · · · · · · · · · · · ·			
		-	3.22
	COP _d (declared COP)	-	
B) condition (2°C)	COP _d (declared COP) Cdh (degradation coefficient)	- - [kW]	3.22 0.00 4.28
	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity)	-	0.00 4.28
	COP _d (declared COP) Cdh (degradation coefficient)	-	0.00 4.28 4.24
(B) condition (2°C)	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u>	- - [kW] - -	0.00 4.28 4.24 0.00
	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP)	-	0.00 4.28 4.24 0.00 3.92
(B) condition (2°C)	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u>	- - [kW] - -	0.00 4.28 4.24 0.00
B) condition (2°C) C) condition (7°C)	COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity)	- [kW] - - - [kW] - -	0.00 4.28 4.24 0.00 3.92 5.97 0.99
B) condition (2°C) C) condition (7°C)	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP)	- - [kW] - -	0.00 4.28 4.24 0.00 3.92 5.97
B) condition (2°C) C) condition (7°C)	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u>	- [kW] - - - [kW] - -	0.00 4.28 4.24 0.00 3.92 5.97 0.99
B) condition (2°C) C) condition (7°C)	COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh (degradation coefficient)</u> P _{dh} (declared heating capacity)	- [kW] - - - [kW] - -	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53
B) condition (2°C) C) condition (7°C)	COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) Tol (temperature operating limit)	- [kW] - [kW] - [kW] - [kW] - [kW] - [kW] - [*C]	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10
 B) condition (2°C) C) condition (7°C) D) condition (12°C) 	COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient)	- - [kW] - - [kW] - - - [kW] - - -	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75
 B) condition (2°C) C) condition (7°C) D) condition (12°C) 	COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) Tol (temperature operating limit)	- [kW] - [kW] - [kW] - [kW] - [kW] - [kW] - [*C]	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10
B) condition (2°C) C) condition (7°C) D) condition (12°C) (E) Tol (temperature operating limit)	COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) <u>Cdh</u> (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared heating capacity)		0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96 55
B) condition (2°C) C) condition (7°C) D) condition (12°C) (E) Tol (temperature operating limit)	COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared heating capacity) COP _d (declared heating capacity) COP _d (declared heating capacity) COP _d (declared heating capacity) COP _d (declared COP)		0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96
 (B) condition (2°C) (C) condition (7°C) (D) condition (12°C) 	COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) P _{dh} (declared Peating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared COP) COP _d (declared Peating capacity) COP _d (declared COP) COP _d (declared COP) WTOL (Heating water Operation Limit) T _b _V		0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96 55
(B) condition (2°C) (C) condition (7°C) (D) condition (12°C) (E) Tol (temperature operating limit)	COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared COP) WTOL (Heating water Operation Limit) Tblv P _{dh} (declared heating capacity)	- [kW] [kW] [kW] [kW] [kW] [kW] [%C] [%C] [*C] [*C]	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96 55 -7 6.82
(B) condition (2°C) (C) condition (7°C) (D) condition (12°C) (E) Tol (temperature operating limit) (F) No label found for faw.tbivalent.temperaturee.	COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) P _{dh} (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared heating capacity) COP _d (declared COP) COP _d (declared COP) WTOL (Heating water Operation Limit) Tblv P _{dh} (declared heating capacity) COP _d (declared cOP) WTOL (Heating water Operation Limit) Tblv P _{dh} (declared heating capacity) COP _d (declared COP)		0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96 55 -7
B) condition (2°C) C) condition (7°C) D) condition (12°C) (E) Tol (temperature operating limit)	COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared heating capacity) COP _d (declared COP) Cdh (degradation coefficient) Tol (temperature operating limit) P _{dh} (declared COP) WTOL (Heating water Operation Limit) Tblv P _{dh} (declared heating capacity)	- [kW] [kW] [kW] [kW] [kW] [kW] [%C] [%C] [*C] [*C]	0.00 4.28 4.24 0.00 3.92 5.97 0.99 4.53 8.03 0.99 -10 6.75 2.96 55 -7 6.82

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals. Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu.' Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.