Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump space heater		No label found for faw.heatpump.single	GT-SKR050KBDC-M3
Space Heating	Energy efficiency class 55°C (High temp. app.) Energy efficiency class 35°C (Low temp. app.)	-	A++ A+++
verage climate (Design temperature = -10°C)	Energy eniciency class 35 C (Low temp. app.)	-	
Space heating 55°C	Prated (declared heating capacity) @ -10°C	[kW]	16.44
	Seasonal space heating efficiency $(\eta_{\mbox{\scriptsize S}})$	[%]	135.0
	Annual energy consumption	[kWh]	10032
Space heating 35°C off peak operation function integrated in Heat pump	Prated (declared heating capacity) @ -10°C	[kW]	15.75
	Seasonal space heating efficiency $(\eta_{\mbox{\scriptsize S}})$	[%]	184.0
	Annual energy consumption	[kWh] Y/N	6962 N
colder climate (Design temperature = -22°C)			
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	15.44
	Seasonal space heating efficiency (η_S)	[%]	106.0
	Annual energy consumption	[kWh]	11782
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	14.75
	Seasonal space heating efficiency $(\eta_{\mbox{\scriptsize S}})$	[%]	143.5
	Annual energy consumption	[kWh]	8320
Warmer climate (Design temperature = 2°C) Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	18.44
	14.04	[%]	176.0
	Seasonal space heating efficiency (n _S) Annual energy consumption	[kWh]	8537
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	17.75
		[%]	239.2
	Seasonal space heating efficiency (n _S) Annual energy consumption	[kWh]	6057
ound Power (*)	Ailitual effergy consumption	[dB(A)]	64
codesign technical data	Air-to-water heat pump:	Y/N	Yes
Product description	Water-to-water heat pump:	Y/N	No
	Brine-to-water heat pump:	<u>Y/N</u> <u>Y/N</u>	No No
	Low-temperature heat pump: Equipped with a supplementary heater:	Y/N	No
uir to water unit	For heat pump combination heater:	Y/N 3	No 5900
Brine/water to water unit	Rated airflow (outdoor) Rated water/brine flow (outdoor H/E)	_{[m} 3 _{/h]}	
Other	Capacity control	[m - /n]	Inverter
	POff (Power consumption Off mode)	- [kW]	0.020
		[kW]	0.020
	Pto (Power consumption Thermostat off mode)	[kW]	0.020
	P _{Sb} (Power consumption Standby mode)		
	PCK (Power crankcase heater model)	[kW]	0.038
	Q _{elec} (Daily electricity consumption)	[kWh]	/
	Qfue (Daily fuel consumption)	[kWh]	/
art load conditions space heating average climate			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	13.93
	COP _d (declared COP)		3.27
	Cdh (degradation coefficient)	-	0.00
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	9.20
	COP _C (declared COP)	-	4.60
	Cdh (degradation coefficient)	-	0.00
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	8.82
	COP _d (declared COP)		5.46
	•		0.99
(D) condition (12°C)	Cdh (degradation coefficient) Pdh (declared heating capacity)	[kW]	9.16
		-	8.08
	COP _d (declared COP)		0.99
(E) Tol (temperature operating limit)	Cdh (degradation coefficient) Tol (temperature operating limit)	- [°C]	-10
	P _{dh} (declared heating capacity	[kW]	13.74
	COP _d (declared COP)	-	2.91
	WTOL (Heating water Operation Limit)	[°C]	55
(F) No label found for faw.tbivalent.temperaturee.	Tblv	[°C]	-7
	Pdh (declared heating capacity)	[kW]	13.93
		-	3.27
	COP _d (declared COP)		J.E1
apacity of the back-up heater integrated in the unit	P _{SUP} back-up heater (@Tdesignh: -10°C)	[kW]	
		[kW]	2.02

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu.'

Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.