

Product Information

Energy labelling Regulation: (EU) 811/2013

Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump space heater		No label found for faw.heatpump.single.	GT-SKR050KBDC-M290T
Space Heating	Energy efficiency class 55°C (High temp. app.)	-	A++
	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Average climate (Design temperature = −10°C)			
Space heating 55°C	Prated (declared heating capacity) @ −10°C	[kW]	13.305
	Seasonal space heating efficiency (ηS)	[%]	141.6
	Annual energy consumption	[kWh]	7603
Space heating 35°C	Prated (declared heating capacity) @ −10°C	[kW]	15.204
	Seasonal space heating efficiency (ηS)	[%]	177.2
	Annual energy consumption	[kWh]	6973
off peak operation function integrated in Heat pump		Y/N	N
Colder climate (Design temperature = −22°C)			
Space heating 55°C	Prated (declared heating capacity) @ −22°C	[kW]	12.29
	Seasonal space heating efficiency (ηS)	[%]	110
	Annual energy consumption	[kWh]	8942
Space heating 35°C	Prated (declared heating capacity) @ −22°C	[kW]	14.28
	Seasonal space heating efficiency (ηS)	[%]	138
	Annual energy consumption	[kWh]	8319
Warmer climate (Design temperature = 2°C)			
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	15.31
	Seasonal space heating efficiency (ηS)	[%]	184.5
	Annual energy consumption	[kWh]	6744
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	17.20
	Seasonal space heating efficiency (ηS)	[%]	230
	Annual energy consumption	[kWh]	6098
Sound Power (*)		[dB(A)]	70
Ecodesign technical data			
Product description	Air-to-water heat pump:	Y/N	Yes
	Water-to-water heat pump:	Y/N	No
	Brine-to-water heat pump:	Y/N	No
	Low-temperature heat pump:	Y/N	No
	Equipped with a supplementary heater:	Y/N	No
	For heat pump combination heater:	Y/N	No
Air to water unit	Rated airflow (outdoor)	[m³/h]	5900
		3	
Other	Capacity control	-	Inverter
	POff (Power consumption Off mode)	[kW]	0.010
	Pto (Power consumption Thermostat off mode)	[kW]	0.029
	PSb (Power consumption Standby mode)	[kW]	0.010
	PCK (Power crankcase heater model)	[kW]	0.040
	Qelec (Daily electricity consumption)	[kWh]	/
	Qfuel (Daily fuel consumption)	[kWh]	/
Part load conditions space heating average climate			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	13.449
	COPd (declared COP)	-	2.97
	Cdh (degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	8.189
	COPd (declared COP)	-	4.61
	Cdh (degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	8.087
	COPd (declared COP)	-	5.73
	Cdh (degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	9.523
	COPd (declared COP)	-	7.87
	Cdh (degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	−10
	Pdh (declared heating capacity)	[kW]	12.993
		-	2.51
	COPd (declared COP)		
WTOL (Heating water Operation Limit)		[°C]	55
(F) No label found for faw.tbivalent.temperaturee.	Tblv	[°C]	-7
	Pdh (declared heating capacity)	[kW]	13.449
	COPd (declared COP)	-	2.97
Capacity of the back-up heater integrated in the unit	Psup back-up heater (@Tdesignh: −10°C)	[kW]	
Supplementary capacity at P_design	Psup (@Tdesignh: −10°C)	[kW]	2.211

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.
Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3
This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer.
Depending on your application and the product selected an additional supplementary heater may have to be installed.