Energy labelling Regulation: (EU) 811/2013 Ecodesign Regulation: (EU) 813/2013

PRODUCT FICHE

Heat pump space hea	ater	No label found for faw.heatpump.single	GT-SKR030KBDC-S
pace Heating	Energy efficiency class 55°C (High temp. app.)	<u>-</u>	A++
verage climate (Design temperature = -10°C)	Energy efficiency class 35°C (Low temp. app.)	-	A++
Space heating 55°C	Prated (declared heating capacity) @ -10°C	[kW]	10.86
		[%]	127.4
	Seasonal space heating efficiency (η _S		
Space heating 35°C	Annual energy consumption	[kWh] [kW]	6882 11.86
	Prated (declared heating capacity) @ -10°C		100.0
	Seasonal space heating efficiency (η_S)	[%]	163.6
	Annual energy consumption	[kWh]	5883
off peak operation function integrated in Heat pump Colder climate (Design temperature = -22°C)		Y/N	_N
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	9.86
	Seasonal space heating efficiency (η _S)	[%]	99.4
	· ·	TIANIA	7960
Space heating 35°C	Annual energy consumption Prated (declared heating capacity) @ -22°C	[kWh] [kW]	10.86
	rated (assumed meaning supposity) @ 22 0	F0/1	107.0
	Seasonal space heating efficiency (η _S)	[%]	127.6
	Annual energy consumption	[kWh]	_6871
Warmer climate (Design temperature = 2°C) Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	12.86
	rated (decided heating capacity) @ 2 0	F0/1	105.0
	Seasonal space heating efficiency (η_S)	[%]	165.6
	Annual energy consumption	[kWh]	6303
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	13.86
	Seasonal space heating efficiency (η_S)	[%]	212.7
	Annual energy consumption	[kWh]	5311
ound Power (*)		[dB(A)]	_61
Ecodesign technical data Product description	Air-to-water heat pump:	Y/N	Yes
	Water-to-water heat pump:	Y/N	No No
	Brine-to-water heat pump:	Y/N	No
	Low-temperature heat pump: Equipped with a supplementary heater:	Y/N Y/N	No No
	For heat pump combination heater:	Y/N	No
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3300
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	[m ³ /h]	
Other	Capacity control	<u>-</u>	Inverter
	POff (Power consumption Off mode)	[kW]	0.020
	P _{†O} (Power consumption Thermostat off mode)	[kW]	0.020
	1 [O (i ower consumption memostation mode)	[kW]	0.020
	P _{Sb} (Power consumption Standby mode)	[[[]]	0.020
	PCK (Power crankcase heater model)	[kW]	0.038
	Qelec (Daily electricity consumption)	[kWh]	/
		[IAMb]	/
	Q _{fue} (Daily fuel consumption)	[kWh]	
art load conditions space heating average climate		TI AATI	40.40
(A) condition (-7°C)	Pdh (declared heating capacity	[kW]	10.49
	COP _C (declared COP)	-	2.93
	Cdh (degradation coefficient)	-	0.00
B) condition (2°C)	P _{CI} h (declared heating capacity)	[kW]	6.98
		-	4.05
	COP _d (declared COP)		
C) condition (7°C)	Cdh (degradation coefficient)	- ILVAN	0.00 5.98
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	9.90
	COP _d (declared COP)	-	5.04
	Cdh (degradation coefficient)	-	0.99
(D) condition (12°C)	P _{Ch} (declared heating capacity)	[kW]	6.74
	5	-	6.69
	COP _d (declared COP)		
(F) Tol (temperature operating limit)	Cdh (degradation coefficient) Tol (temperature operating limit)	- [°C]	0.99 10
(E) Tol (temperature operating limit)	Pdh (declared heating capacity	[kW]	10.09
			2.79
	COPd (declared COP)		2./3
E) No lob of formal form	WTOL (Heating water Operation Limit)	[°C]	55
(F) No label found for faw.tbivalent.temperaturee.	^T blv	[°C]	-7
		[kW]	10.49
	Pdh (declared heating capacity)		
	Pdh (declared heating capacity)		2 93
	Pdh (declared heating capacity) COPd (declared COP)	-	2.93
apacity of the back-up heater integrated in the unit	COP _d (declared COP)	- [kW]	2.93
	COP _d (declared COP) P _{SUP} back-up heater (@Tdesignh: ~10°C)		
Capacity of the back-up heater integrated in the unit Supplementary capacity at P_design	COP _d (declared COP)	[kW]	2.93

Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.

Energy labels and product fiches for additional combinations, packages and other products can be found on 'energylabel.daikin.eu.'

Sound power level in heating mode, measured according to the EN15036 for combustion boilers and EN 12102 for heat pumps under conditions of the EN ISO 3746, accuracy class 3 This data is for comparison of Energy efficiencies according to Regulation (EU) 2017/1369, for correct selection of products for your application, contact your dealer. Depending on your application and the product selected an additional supplementary heater may have to be installed.